About us



Zhe Jiang Tian Qi New Material Technology Co., Ltd. is one of the largest high-tech environmental protection enterprises in China. Located in Si 'an Industrial Zone, Changxing County, Huzhou City, Zhejiang Province; it is adjacent to the new 318 National Road and 204 Provincial Road. It is only 3 kilometers from the HuYu expressway Si an export. It is less than 10 kilometers from the beautiful xian sheng lake national wetland park. The traffic conditions are very convenient and Nobake Furan Resin is unique.

The main products of Tianqi company are hot curing furan resin, self-hard furan resin, alkaline phenolic resin and all kinds of curing agents, cast steel coating, cast iron coating, slag removing agents,s and so on. The annual output of cast iron resin is 30000 tons, cast steel resin is 15000 tons, hot curing resin and alkaline phenolic resin is 10000 tons, curing agents more than 30000 tons, and powder coating more than 5000 tons, and the annual output value reaches hundreds of millions of RMB. The products can satisfy users' requirements and provide supporting services for enterprises.

The company has established long-term and stable business cooperation with Ningbo Sun

and moon group, Ningbo Yongxiang Foundry Co., Ltd., Zhejiang Jiali Wind Energy
Technology Co., Ltd., and so on. Products occupy more than seventy percent of Zhejiang's
market share and continue to extend to Shanghai, Fujian, Jiangsu, Hubei, Anhui, Jiangxi, and
other places.

Tian Qi, through many years of hard work, started from zero, insisting on honesty as the quality based, mutual benefit, and friends as respect for <u>Slag Remover Agent</u>, experienced the test in the fierce market competition, and won the high trust and long-term cooperation of the leading enterprises and users who enjoyed the reputation of the casting industry, and the enterprise has developed rapidly. Brand reputation, crane, and sales network have been expanding. It has laid a solid foundation for the world to sell products to the world.

Products

Heat Cured Resin



Product Introduction:

Ratio:(weight ratio) sand: resin = 100:(0.8 ~ 2) resin: curing agent=100:(30~50)

Curing agent: different curing agents can be selected according to different temperatures.

Curing agents can be divided into spring and autumn. Seasonal GH03, summer GH04, GH05 and winter GH08, GH09 and so on several models.

Mixing sand: mix sand with curing agent for 5 minutes, then mix with resin for 2 minutes.

Caution: furan resin and curing agent must not be directly contacted to prevent explosion. If contact with skin carelessly, rinse with water in time.

Mold Release Agent



Product Introduction:

The mould release agent is made of high quality materials. It has the advantages of fast evaporation and high efficiency. It can be reused many times without sticking. Can effectively solve the resin sand, water glass sand, oil sand, grease sand and other sticky mold problems, suitable for sprayed or brush to the mold or core box surface, the first brush

2-3 times, after each brush, volatilization $5 \sim 20$ minutes can be modeled, once each brush can be used 5-15 times depending on the degree of complex or type of pattern.

Japanese Slag Remover Agent



Product Introduction:

Description:

The slag remover can effectively accumulate the slag in the molten iron, remove thoroughly, reduce the slag inclusion defects of the castings, and obtain high quality castings.

Contact us

Company name: Zhe Jiang Tian Qi New Material Technology Co., Ltd.

Web: https://www.tqnewmaterial.com/

ADD: Si'an Industrial Zone, Changxing County, Huzhou City, Zhejiang Province

Phone: 13606713008

Email: rachelwang@zjtianqi.cn

Tip: 313000